



### Technical Specifications

§ <b>Engine Type</b>	Air-cooled, 4-stroke, V-twin, Vertical shaft, OHV
§ <b>Number of cylinders</b>	2
§ <b>Bore x stroke</b>	78 x 76 mm
§ <b>Displacement</b>	726cm <sup>3</sup>
§ <b>Max. power</b>	14.1 kW (18.8 hp) / 3600 rpm
§ <b>Max. torque</b>	53.2 Nm (39.2 ft.lbs) / 1800 rpm
§ <b>Fuel tank capacity (litres)</b>	
§ <b>Oil capacity (litres)</b>	2.1 litres
§ <b>Dry weight</b>	46.6 Kg
§ <b>Dimensions (L x W x H) (mm)</b>	479 x 448 x 565

### Type

- § **4 Stroke**
- § **Air Cooled**
- § **V Twin**
- § **Overhead Valve**
- § **Vertical Shaft**

### Features

- § **90 degree V-twin**
- § **Automatic compression release**
- § **Cast iron cylinder liners**
- § **Dual stage canister air filter**
- § **Electronic spark ignition**
- § **Heavy duty shift type starter**
- § **High performance lubrication system**
- § **Metal engine cover**
- § **Overhead V-valves**
- § **Rotating grass screen**
- § **Twin barrel, internally vented carburetor with fuel shut-off solenoid**

### Options

### Performance curves

The power rating of this engine is the Net power rating tested on a production engine and measured in accordance with SAE J1349. Actual power output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.



